

# PRODUCT CHARACTERISTIC SHEET and COC

**PLEASE READ BEFORE USING!**

**Material: STUBBL**

**Part Nos: STB18520CL, STB181320CL, STB182020CL, STB182720CL, STB185420CL**

**General Description:** This heavily textured clear flexible laminate provides anti-slip characteristics to the surface or media it is applied to. Stubbl works when it is dry or wet and therefore is recommended for watercraft and tubs as well as bikes and other recreational vehicles. This film exceeds OSHA & ADA Standards for non-slip protection on hazardous surfaces. Certified as "High Traction" by the NFSI.

Thickness:	20 mil embossed vinyl with 2 mils of adhesive	<b>Adhesive Properties:</b> Permanent Acrylic
Outdoor Life:	2 years	
Shelf Life:	1 years stored at 70° F & 50%RH	
Service Temperature Range:	-20° F to 175° F (-32°C to 40°C)	
Minimum Application Temp.:	50° F	

**Tests performed | results:**

Ultimate Peel from	Average Results	Test Method PSTC - 101
Stainless Steel	55 oz/in	15 min dwell, (66N/100mm)
Stainless Steel	75 oz/in	24 hr dwell, (82N/100mm)
Powder Coat Paint*	40 oz/in	15 min dwell, (44N/100mm)
Powder Coat Paint*	55 oz/in	24 min dwell, (60N/100mm)
Polyethylene	20 oz/in	15 min dwell, (22N/100mm)
Polyethylene	25 oz/in	24 hr dwell, (27N/100mm)
Expected Shear Room Temp (< hours)	< 5 hours	Test Method PSTC - 107 1/2" x 1/2" x 1000g
Tack (gm/sq cm)	< 5 inches	Test Method PSTC - 6 Rolling ball tack
Coefficient of Friction (Kinetic)	0.9 1 1	Test Method ASTM D1894 Dry Rubber Wet Rubber Wet Leather

**CERTIFICATE OF CONFORMANCE (COC)**

Sold to:			Lot No.:	
Buyer:		PO#	Supplier's Authorized Rep.:	
Supplier:	Graphic Marking Systems	MFR Part No:	Top of the page	Title:
MFR Date:		Ship Date:		Date:

**Recommended Application Techniques:**

Apply to clean, dry, lubricant-free surfaces. If you intend to apply Stubbl to solvent ink jet prints, we strongly suggest that you let the prints dry for at least an hour before laminating. The end user is responsible for determining the exact "dry times" for the ink and media combination they are using.

**USE A 45° blade or 60° BLADE on any combination of material 8 mil or thicker.**

**Disclaimer:**

This information has been gratuitously provided by Graphic Marking Systems (GMS). Although it is intended to be accurate, Graphic Marking Systems DISCLAIMS ANY AND ALL LIABILITY, EITHER EXPRESS OR IMPLIED. This information is based on many factors beyond Jessup's control, including but not limited to the completeness and accuracy of information received, or the conditions prevailing when operations were observed and/or sampled. In choosing to rely on or use this information, you assume all risk including the results obtained and agree to indemnify Graphic Marking Systems against any and all claims. All recommendations or suggestions must be evaluated by you to determine their applicability or suitability for your particular program. GMS is not engaged in rendering legal or other professional service and if such service is required, a competent professional should be retained. Any information claimed by GMS to be confidential or proprietary is not to be disclosed to any third party. GMS0518 Graphic Marking Systems

# Material Safety Data Sheet (MSDS)

<b>Material Name:</b> STUBBL	<b>Company:</b> Graphic Marking Systems Address: 28457 N. Ballard Rd., Suite A1 Lake Forest, IL 60045 Phone: 847-582-9276 Fax: 847-582-9282
<b>Part Nos:</b> STB18520CL, STB181320CL, STB182720CL, STB185420CL	
Date Prepared: 5/21/2018	
<b>General Description:</b> Heavily textured clear flexible laminate .	

<b>Composition and information on ingredients:</b> Individual components of this product do not contribute to any known hazards.	<b>UL Recognized:</b>	<b>NO</b>
	<b>ROHS Compliant:</b>	<b>YES</b>
	<b>REACH Compliant:</b>	<b>YES</b>

<b>Hazards Identification:</b>
POTENTIAL HEALTH EFFECTS: None
ACUTE: No significant toxic hazard. When burned may produce toxic fumes.
CHRONIC: No significant toxic hazard.
None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA, or ACGIH as a carcinogen.

<b>First Aid Measures:</b>	
Emergency and First Aid Procedures:	
<b>ROUTES OF ENTRY:</b>	
Inhalation: N/A	Skin: N/A
Eyes: N/A	Ingestion: N/A

<b>Fire Fighting Measures:</b>	
Flash Point:	N/A
Method Used:	N/A
Auto-ignition Temperature	N/A
Flamable limits in Air % by Volume:	LEL: N/A, UEL: N/A
Extinguishing Media:	Use extinguisher with class A agents or water
Unusual Fire and Explosion Hazards:	None
Special Fire Fighting Procedures: In case of fire, use self-contained breathing apparatus and full protective equipment - all fires liberate toxic gases.	

<b>Accidental Release Measures:</b> N/A
<b>Handling and Storage:</b> No special handling required other than storing away from excessive heat sources.

<b>Exposure Controls and Personal Protection:</b>	
Respiratory Protection:	None required
Skin Protection:	No precautions required
Eye Protection:	None applicable
Exposure Guidelines:	None established
Engineering Controls:	None required

<b>Physical and Chemical properties: NA = Not Applicable, or Not Available</b>			
Vapor Pressure (mm Hg)	N/A	Boiling Point:	N/A
Vapor Density (air = 1):	N/A	Melting Point:	N/A
Appearance and odor:	N/A	Reactivity of water:	N/A
Specific Gravity (H 0=1)	N/A	Solubility in water:	N/A

<b>Toxicological Information:</b> Not determined
---

<b>Stability and Reactivity:</b>	
Stability:	Stable
Conditions to avoid:	Fire or Excessive Heat

<b>Ecological Information:</b> No Data Available
--

<b>Hazardous Decomposition By-Products:</b>	
Hydrocarbons, Carbon dioxide, Carbon monoxide, Toxic vapor, During Combustion	
<b>Hazardous Polymerization:</b>	Will not occur.

<b>Transport Information:</b>	
TRANSPORTATION AND HAZARDOUS MATERIALS DESCRIPTION: Not a hazardous material for DOT shipping.	

<b>Regulatory Information:</b>	
US Federal Regulations 311/312 Hazard Categories Fire Hazard – No Pressure hazard – No Reactivity Hazard – No Immediate Hazard – No Delayed Hazard – No	
Chemical Inventories – These products are articles as defined by TSCA regulations and are exempt from TSCA inventory listing requirements.	

<b>Disposal Considerations:</b> Waste Disposal: Dispose of in accordance with Local, State and Federal regulations.
--

<b>Other Information:</b>  The information contained herein is based on the data available to Graphic Marking Systems, and is believed to be correct. However, Graphic Marking Systems makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Graphic Marking Systems assumes no responsibility for injury from the use of the product described herein.
---

<b>CALIFORNIA PROPOSITION 65:</b> Restricted substances have not been intentionally added to this product nor are they known to be present above established limits. This product has not been specifically tested for the presence of these substances.
--